

 Genuine Mobile Computer

NBW-35

Maximum Mobility in Your Hand

- Optimal Combination of Mobility and Performance
- Superior Durability and Reliability
- Versatile Data Collection Options
- Fast and Reliable Network Connections
- Advanced Features and Flexibility
- All-round Mobile Computer



sewoo

Specifications

PDA SPECIFICATION

CPU	PXA 320 806MHz (Marvell)	
Memory	512MB RAM, 1GB NAND Flash	
OS	WinCE 5.0, Windows Mobile 6.5	
LCD	8.9cm(3.5 Inch) Color TFT LCD (256K Color) 240 x 320 Resolution & Touch Panel	
WAN	GSM/GPRS/EDGE (850/900/1800/1900 MHz) UMTS/HSPA+ (800/850/900/1700/1900/2100 MHz)	
WLAN	IEEE 802.11 a/b/g/n with CCX v4	
PAN	Bluetooth v2.1 + EDR Class 2	
GPS	Embedded GPS	
Antenna	Internal Antenna for all wireless modules (WAN, WLAN, GPS)	
RFID	HF : 13.56 MGz ISO/IEC 14443A/B, 15693, Mifare UHF : 900MHz Class 1 Gen2.ISO18000-6C	
Digital Camera	3.0M Pixels AF Digital Camera / LED Flash	
Barcode Scanner	Laser	1D Barcode : UPC/EAN/KAN, Code 39/93/128, I2 of 5, Codabar, etc
	CMOS	1D Barcode : UPC/EAN/KAN, Code 39/93/128, I2 of 5, Codabar, etc 2D Barcode : PDF417, QR code, Datamatrix, Maxi code, etc
Interface	USB 2.0 Client, USB 1.1 Host, RS-232C & Ethernet (via cradle)	
Keypad	38 Key Numeric Keypad 53 Key QWERTY Keypad	
Audio	Loud Speaker (Back) & Receiver (Front), MIC, 3.5Ø Headset Jack	
Voice and Audio	voWWAN, voWLAN, PTT, Volp-ready	
Notification	Vibrator & LED	
Expansion Slot	Micro SD (Maximum 32GB) / USIM / SAM slot	
Battery	Rechargeable Lithium Ion 3.7V 4000mAh	
Accessories	Pick-type Stylus, String, Hand Strap	
Reliability	Temperature	Operating : -20°C ~ +50°C (-4°F ~ +122°F) Storage : -30°C ~ +70°C (-22°F ~ +158°F)
	Humidity	93% at +50°C (122°F) non condensing
	Drop Test	1.8m (6 ft) drop on all faces, edges & corners per MIL-STD-810G
	IP rating	IP65 per IEC Sealing Specifications
	ESD	12KV Air / 8KV Touch
Dimension	163 mm x 76 mm x 36.5 mm	
Weight	350 g (with battery)	

PERIPHERAL SPECIFICATION

1 Slot / 4 Slot Cradle	Charger : Charge device(s) and additional battery Interface : USB type (USB B-type Port) / RS-232C / RJ45 (Option) Input : AC 100V - 240V (Universal)
Vehicle Cradle	Charger, USB, RS-232C

※ All specifications and designs are subject to change without notice.

Accessories

Optional



Single Slot Cradle



4 Slot Cradle



Snap-On IO



Gun Trigger



Travel Charger

J.stephen

www.miniprinter.com

J.STEPHEN Co., Ltd.

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

TEL. +82-31-8077-5000 / FAX. +82-31-459-8880 / E-Mail : sales@miniprinter.com