


Mobile Computer

# HF550

## Reasonable Choice in Hyper-Connected Era

- Compact & Sleek Design
- Enhanced Durability & Lifecycle
- Supported by BOS™ Enterprise Solutions
- High-Capacity Smart Battery, Power for Hours
- Touch in Every Condition



**OS**  
Android 10  
with GMS



**Performance**  
Octa-Core Processor



**Wireless**  
Wifi, Bluetooth  
Support



**Battery**  
3.8V, 4000mAh  
Smart Battery



**Drop Resistance**  
Multiple 1.2 m (4 ft) drop  
per MIL-STD 810G



**Sealing**  
IP67 (WWAN)  
IP54 (WiFi Only)



**Operation Temp**  
-10°C to 50°C  
14°F to 122°F



**Camera**  
13MP Autofocus  
with flash



**Display**  
5.45" HD+  
(1440x720)



**Gloved Touch**  
Multi Touch Support –  
Wet, Stylus, Glove

## • Key Features

### Compact & Sleek Design

Forget the idea that Industrial mobiles are always big and heavy. Bluebird beautified HF550's appearance with a compact and light form factor. Reduce fatigue and make better working environment with HF550.

### Enhanced Durability & Lifecycle

HF550 is designed as an enterprise device for work. With IP67 sealing, HF550 can be used in dust, dirt and water and is designed to withstand to tumbles and 1.2m drops. Unlike consumer smartphones, Bluebird HF550 will be provided as long as customers need, up to 5 years, making you reduce the cost and continue your business steadily.

### Supported by BOS™ Enterprise Solutions

Bluebird BOS™ (Business Optimizing Solutions) is to support from development to maintenance as device management on enterprise level. You can access specialized applications in Business such as PTT Express, Wi-Fine™, Provisioning & Staging solutions without additional cost. Bluebird provides these premium services based on its know-how and experience of over 2 decades.

### High-Capacity Smart Battery, Power for Hours

With 4000mAh battery, HF550 has advantages on running times with using enterprise-oriented application requiring more power because PowerManager™, one of Bluebird BOS™ Solutions, helps you use battery in a smart way.

### Touch in Every Condition

Keep your gloves on when working with HF550. Bluebird capacitive multi-touch works in every condition: in wet conditions & with gloves.

### Industry & Applications

#### Retail

- Customer Engagement
- BOPIS (Buy online, Pick up in store)
- Shelf Management
- Backroom Management

#### Warehouse Management

- Receiving
- Stocking
- Shipping

#### Hospitality

- Order Taking

#### Healthcare

- EMR/EHR
- Pharmacy Management

### BOS™ Solutions & Software

- BOS™ Provisioning
- BOS™ Staging
- BOS™ Kiosk
- BOS™ Virtual Key
- BOS™ Enterprise Keyboard
- BOS™ VoIP, PTT, PTT Express
- BOS™ EMM
- BOS™ Wi-Fine™  
(WiFi analyze application)
- BOS™ SecureID

### 3<sup>rd</sup> Party Solutions Integration

- EMM : Airwatch, MobileIron, Mobicontrol, IBM Mass360, XenMobile
- PTT : ESChat, Zello, IMPTT, EveryTalk, AirPTT

### Bluebird Warranty Service (up to 5 years)

- BluebirdCare™
- BluebirdCare™ TCS
- Bluebird SecureCare™ AirPTT

# Specifications

PERFORMANCE CHARACTERISTICS	
CPU	2.2 GHz Octa Core Processor
Operating System	Android 10 ; Upgradeable to Android 14
Memory	4GB RAM / 32GB Flash
PHYSICAL CHARACTERISTICS	
Dimensions (L x W x D)	151.8 x 74.5 x 12.2 mm
Weight	200g
Display	5.45" HD+ (1440 x 720), TFT-IPS
Imager Window	Corning® Gorilla® Glass
Touchpanel	Capacitive multi-touch / Stylus, Glove, Wet
Backlight	LED backlight
Power	Integrated Battery 3.8V / 4000mAh BOS™ PowerManager Station
Expansion Slot	MicroSD 32GB SDHC, up to 128GB SDXC
SIM / SAM	Hybrid Dual SIM Slot (2 Nano SIM or 1 Nano SIM / 1 Micro SD) 1 Nano SIM is supported by micro SD Card Slot
Interface	USB Type C Connector (USB 2.0) Docking Connector (Charging)
Notification	Audible tone; multi-color LEDs; vibration
Keypad	On-screen keypad and Enterprise Keyboard power button; volume up/down buttons 1 Action key
Voice and Audio	Dual noise-cancelling microphones; High-quality speaker phone, 3.5mm headset jack
PTT Hot Key	Support – available Active Key
WIRELESS WAN DATA AND VOICE COMMUNICATIONS	
Radio Frequency Band	(Optional) EMEA, Korea, Thailand, India - LTE FDD: B1/B3/B5/B7/B8/B20 - LTE TDD: B38/B40/B41 - WCDMA: B1/B5/B8 - GSM/EDGE : B3/B8 Latin America, Australia, ANZ, Taiwan - LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 - LTE TDD: B40 - WCDMA: B1/B2/B5/B8 - GSM/EDGE : B2/B3/B5/B8 Japan - LTE FDD: B1/B3/B8/B18/B19/B26 - LTE TDD: B41 - WCDMA: B1/B6/B8/B19 North America - LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71 - WCDMA: B2/B4/B5 China - LTE FDD : B1/B3/B5/B8 - LTE TDD : B38/B39/B40/B41 - WCDMA : B1/B8 - GSM/EDGE : B3/B8
GPS	(for WWAN only) A-GPS, GLONASS, BEIDOU, Galileo

WIRELESS LAN	
Radio	802.11 a/b/g/n/ac/d/h/i/k/r/w
Data Rates	5GHz: 802.11a/n/ac — up to 433Mbps; 2.4GHz: 802.11b/g/n — up to 72.2Mbps
Security and Encryption	WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA/WPA2 Enterprise (TKIP, and AES) - EAPTTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PE APv0- MSCHAPv2, PE APv1-EAP-GTC, EAP Fast and LEAP
WIRELESS PAN	
Bluetooth	Bluetooth 5.0 BLE , Class 2
COMMUNICATION AND MESSAGING	
VoIP / PTT	
DATA CAPTURE	
Scanning	(Optional) Camera barcode reading
Camera	Rear : 13MP Autofocus with flash Front : 5MP Fixed Focus
NFC	ISO 14443 Type A and B; F; FeliCa, and ISO 15693 cards, MiFare
SENSOR	
Light Sensor	Ambient Light
Motion Sensor	Proximity, Gyro, Accelerometer, E-Compass
USER ENVIRONMENT	
Operating Temp	-10°C to 50°C / 14°F to 122°F
Storage Temp	-30°C to +70°C / -22°F to +158°F
Humidity	95% non-condensing
Drop Spec	1.2m / 4ft. drop per MIL-STD 810G
Tumble Spec	300 tumbles, 1.6 ft./0.5 m
Sealing	WiFi SKU : IP54 WWAN SKU : IP67
Vibration	4G peak, 5 Hz to 2 kHz, 1 hour duration per axis
Thermal Shock	-40° C to 70° C / -40° F to 158° F rapid transition 10 cycles (1 cycle = 1.25 hours at -40°C and 1.25 hours at 70°C)
Electrostatic Discharge (ESD)	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge
ACCESSORIES	
In-box	Wall Adapter, USB Cable, SIM tooling pin
Additional	Wrist Strap, Protective Film, Protective Case (TBD), Multi-slot charging Cradle (TBD)

\* Specifications are subject to change without notice.